

View Online at <https://aerobasegroup.com/nsn/5930-00-133-8611>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 0.606 inches and 0.626 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.168 inches and 0.208 inches

**Overall Height:**

0.745 inches

**Overall Width:**

Between 0.306 inches and 0.326 inches

**Body Length:**

Between 0.606 inches and 0.626 inches

**Body Width:**

Between 0.306 inches and 0.326 inches

**Body Height:**

0.645 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.091 inches

**Actuator Style:**

Round

**Actuator Height:**

0.050 inches

**Actuator Free Position Height:**

Between 0.405 inches and 0.445 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 5.0 ounces and 17.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0