

View Online at <https://aerobasegroup.com/nsn/5930-00-133-8644>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

7.812 inches

**Shaft Diameter:**

0.250 inches 2nd actuator

**Shaft Length:**

0.375 inches 1st actuator

**Overall Diameter:**

1.312 inches

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

7

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 1st actuator

**Shaft Type:**

Round, hollowed 2nd actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

60.0 degrees 2nd actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:**

Clip and rotor surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0