## NSN 5930-00-133-8678



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-133-8678 **Body Style: Bushing mounted Overall Length:** 2.230 inches **Overall Height:** 3.061 inches **Overall Width:** 1.065 inches **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.781 inches **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.120 inches **Housing Bushing Length:** 0.657 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** Between 6.0 ounces and 12.0 ounces **Actuator Movement:** Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc **Thread Series Designator:** Unef **Terminal Type And Quantity:** 1 connector, receptacle Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5930-00-133-8678

Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0