NSN 5930-00-133-8707

Flow Switch - Page 1 of 1

Fiig: A048b0



View Online at https://aerobasegroup.com/nsn/5930-00-133-8707 **Overall Length:** 3.250 inches **Overall Width:** 2.620 inches **Mounting Method:** Input port **Features Provided:** Hermetically sealed case Thready Qty Per Inch (tpi): 14 first pressure connection **Contact Action Stimulus:** Increase **Thread Size:** 0.500 inches second pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained **Terminal Type:** Wire loop **Contact Load Current Rating:** 7.0 amperes resistive load second voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 0.91 actuation point gallons per minute and 0.75 deactuation point gallons per minute **Contact Voltage Rating In Volts:** 250.0 ac at sea level second voltage **Special Features:** 90.0 psig system pressure; 125.0 psig proof pressure; pressure drop not to exceed 6 psi at flow rate of 1.0 gpm Media For Which Designed: Liquid **Thread Series Designator:** Npt second pressure connection Shelf Life: N/a **Unit Of Measure: Demilitarization:** No