NSN 5930-00-134-0313

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-134-0313

Hole mounted		
Hazardous Locations/environmental Protection:		
Dustproof		
Overall Length:		
1.940 inches		
Center To Center Distance Between Mounting Facilities Parallel To Length:		
1.000 inches		
Overall Height:		
0.940 inches		
Overall Width:		
0.670 inches		
Body Length:		
1.940 inches		
Body Width:		
0.670 inches		
Body Height:		
0.860 inches		
Unthreaded Mounting Hole Diameter:		
0.140 inches		
Actuator Length:		
1.250 inches		
Actuator Style:		
Leaf		
Actuator Width:		
0.190 inches		
Actuator Free Position Height:		
0.700 inches		
Maximum Voltage Rating In Volts:		
125.0 ac and 28.0 dc		
Inclosure Type:		
Fully enclosed		
Mounting Method:		
Unthreaded hole		
Nonpile-up Contact Arrangement:		
1 pole, double throw, one position momentary single switch unit		
Switch Release Force:		
8.0 ounces		
Switch Actuating Force:		

Actuator Movement:

Between 28.0 ounces and 56.0 ounces

Between 0.225 pretravel inches and 0.010 overtravel inches and 0.020 differential inches

NSN 5930-00-134-0313

Sensitive Switch - Page 2 of 2

Fiig: A053a0



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 4.000 amperes motor dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

Terminal Type And Quantity:	
3 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	