

View Online at <https://aerobasegroup.com/nsn/5930-00-134-0342>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.188 inches

Overall Width:

1.218 inches

Actuator Length:

0.734 inches

Actuator Style:

Roller plunger

Actuator Roller Width:

0.500 inches

Housing Height:

1.250 inches

Housing Length:

2.562 inches

Housing Width:

1.218 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.563 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.875 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 4.0 pretravel degrees and 8.0 overtravel degrees and 1.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

Special Features:

Wire leads are 24 in. Lg

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0