Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-134-0377

xplosion resistant
verall Length:
500 inches
verall Height:
696 inches
verall Width:
366 inches
nthreaded Mounting Hole Diameter:
089 inches single mounting facility
dividual Section Quantity:
ongest Horizontal Distance Between Mounting Centers:
094 inches single mounting facility
ongest Vertical Distance Between Mounting Centers:
178 inches single mounting facility
ounting Method:
racket single mounting facility and unthreaded hole single mounting faci
ctuator Type:
humbwheel single actuator
eatures Provided:
uminated
ontact Voltage Rating In Volts:
8.0 dc at sea level
ounting Facility Pattern:
our position rectangular single mounting facility
witch Actuator Indexing Position Quantity:
0 single actuator
erminal Type:
rinted circuit
ontact Load Current Rating:
25.0 milliamperes resistive load dc at sea level
eadout Indicator Marking:
, 2, 3, 4, 5, 6, 7 single section
ontact Arrangement Truth Table:
ecimal, 1 pole - 10 positions single section
olor:
lack single indicator background
recious Material And Location:
ontact surfaces gold
recious Material:
old

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

