

View Online at <https://aerobasegroup.com/nsn/5930-00-134-0377>

Hazardous Locations/environmental Protection:

Explosion resistant

Overall Length:

0.500 inches

Overall Height:

1.696 inches

Overall Width:

1.366 inches

Unthreaded Mounting Hole Diameter:

0.089 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.094 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.178 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Features Provided:

Illuminated

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

1, 2, 3, 4, 5, 6, 7 single section

Contact Arrangement Truth Table:

Decimal, 1 pole - 10 positions single section

Color:

Black single indicator background

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0