NSN 5930-00-134-5036

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-134-5036

Thread Class:
2a single mounting facility
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
3.570 inches
Overall Diameter:
1.780 inches
Individual Section Quantity:
1
End Application:
Weapon system-aircraft, starlifter c-141
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Threaded stud single mounting facility
Features Provided:
Metallic inclosure
Thread Size:
0.500 inches single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Switch Actuator Indexing Position Quantity:
3 single actuator
Terminal Type:
Screw
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
75.0 amperes inductive load dc at sea level
Style Designator:
Tap, circular, bushing mount
Supplementary Features:
Includes screw 131963, washer ms35337-23, nut 5381233, washer ms35333-44
Thread Series Designator:
Unf single mounting facility
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-00-134-5036

Rotary Switch - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A052b0