NSN 5930-00-134-5262

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-134-5262

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture resistant and salt spray resistant and shock resistant
Overall Length:
4.100 inches
Overall Height:
1.500 inches
Overall Width:
1.500 inches
Body Diameter:
1.500 inches
Bushing Length:
0.340 inches
Body Length:
2.820 inches
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Height:
0.940 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.310 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
144.0 inch-ounces

Switch Actuating Force:

Between 192.0 inch-ounces and 400.0 inch-ounces

Actuator Movement:

Between 20.0 pretravel degrees and 25.0 overtravel degrees and 6.0 differential degrees

NSN 5930-00-134-5262

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0