NSN 5930-00-135-2054

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-135-2054

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 1.406 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.125 inches |
| Overall Height: |
| 1.004 inches |
| Overall Width: |
| 0.553 inches |
| Body Length: |
| 1.000 inches |
| Body Width: |
| 0.513 inches |
| Case Material: |
| Metal |
| Unthreaded Mounting Hole Diameter: |
| 0.136 inches |
| Actuator Length: |
| 0.307 inches |
| Actuator Height: |
| 0.328 inches |
| Actuator Width: |
| 0.217 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 125.0 dc |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 750.000 milliamperes resistive dc and 750.000 milliamperes resistive ac |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5930-00-135-2054

Slide Switch - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A053a0