

View Online at <https://aerobasegroup.com/nsn/5930-00-135-7107>

**Overall Length:**

3.875 inches

**Overall Diameter:**

4.062 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Threaded bushing

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Decrease

**Thread Size:**

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.20/+1.00 actuation point inches of water and +0.20 to 1.00 deactuation point inches of water

**Contact Adjustment Type:**

External deactuation point serrated nut and external actuation point serrated nut

**Contact Stimulus Rating:**

0.45 actuation point inches of water and 0.65 deactuation point inches of water and 0.20 differential point inches of water

**Contact Voltage Rating In Volts:**

24.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Liquid

**Thread Series Designator:**

Nptf all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0