

View Online at <https://aerobasegroup.com/nsn/5930-00-137-0630>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

1.250 inches

**Body Width:**

0.500 inches

**Body Height:**

0.875 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Actuator Length:**

0.859 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

1.181 inches

**Actuator Roller Width:**

0.187 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

14.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Actuator Movement:**

Between 0.150 pretravel inches and 0.015 overtravel inches and 0.033 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 7.000 amperes inductive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:**

8 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0