

View Online at <https://aerobasegroup.com/nsn/5930-00-137-0630>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.875 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Actuator Length:

0.859 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.181 inches

Actuator Roller Width:

0.187 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

14.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.150 pretravel inches and 0.015 overtravel inches and 0.033 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.000 amperes inductive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

8 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0