

View Online at <https://aerobasegroup.com/nsn/5930-00-137-2718>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.626 inches

Body Width:

0.326 inches

Body Height:

0.600 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.091 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.326 inches

Actuator Height:

0.095 inches

Actuator Free Position Height:

0.475 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac and 4.000 amperes motor ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0