NSN 5930-00-137-7347

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-137-7347

# **Thread Class:**

2b single mounting facility

# **Overall Length:**

4.938 inches

# **Overall Height:**

2.812 inches

# **Overall Width:**

2.812 inches

# Individual Section Quantity:

1

## Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section periphery

#### **Throw Quantity:**

11 single section periphery

#### Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

## **Features Provided:**

Actuator knob

#### Thready Qty Per Inch (tpi):

24 single mounting facility

#### **Thread Size:**

0.190 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

125.0 ac at sea level

#### Mounting Facility Pattern:

Four position rectangular single mounting facility

#### Switch Actuator Indexing Position Quantity:

12 single actuator

#### **Terminal Type:**

Screw

#### **Contact Switching Action:**

Breaks before makes single section periphery

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Adjustable stop single actuator

# NSN 5930-00-137-7347

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

7.5 amperes resistive load ac at sea level

**Special Features:** 

Waterproof collar

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0