

View Online at <https://aerobasegroup.com/nsn/5930-00-137-7415>

**Body Style:**

Bushing mounted

**Body Length:**

1.617 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

Between 0.135 inches and 0.197 inches

**Actuator Roller Diameter:**

Between 0.307 inches and 0.317 inches

**Actuator Roller Width:**

0.125 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.438 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

30.0 ounces

**Actuator Movement:**

Between 0.010 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

72.000 in. Lg wire leads

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0