

View Online at <https://aerobasegroup.com/nsn/5930-00-137-7416>

Body Style:

Bushing mounted

Bushing Length:

Between 1.344 inches and 1.406 inches

Body Length:

Between 0.869 inches and 0.931 inches

Body Width:

Between 0.875 inches and 0.937 inches

Body Height:

Between 0.469 inches and 0.531 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.135 inches

Actuator Roller Diameter:

Between 0.307 inches and 0.317 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.438 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.093 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

72.000 in. Lg wire leads

Thread Series Designator:

Un

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0