## NSN 5930-00-138-2316



Flow Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-138-2316 **Overall Height:** 1.250 inches **Overall Width:** 2.000 inches **Body Length:** 4.120 inches **Unthreaded Mounting Hole Diameter:** 0.187 inches **Longest Horizontal Distance Between Mounting Centers: 2.700 inches Longest Vertical Distance Between Mounting Centers:** 1.600 inches **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit **Mounting Method:** Unthreaded hole **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position diagonal **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Wire lead **Contact Load Current Rating:** 500.0 milliamperes resistive load second voltage **Contact Adjustability:** Actuation point adjustable **Contact Adjustment Range:** +0.20 to 15.00 actuation point gallons per minute **Contact Adjustment Type:** External actuation point screw **Contact Voltage Rating In Volts:** 6.0 dc at sea level first voltage Media For Which Designed: Liquid **Style Designator:** Rectangular Shelf Life:

N/a **Unit Of Measure:**--

## NSN 5930-00-138-2316

Flow Switch - Page 2 of 2



em			

No

Fiig:

A048b0