## NSN 5930-00-138-2316

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-138-2316

## **Overall Height:**

1.250 inches

**Overall Width:** 

2.000 inches

## Body Length:

4.120 inches

## **Unthreaded Mounting Hole Diameter:**

#### 0.187 inches

## Longest Horizontal Distance Between Mounting Centers:

2.700 inches

## Longest Vertical Distance Between Mounting Centers:

1.600 inches

## **Operating Tempurature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

## Mounting Method:

Unthreaded hole

## **Contact Action Stimulus:**

Increase

## Mounting Facility Pattern:

Two position diagonal

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

## **Terminal Type:**

Wire lead

## **Contact Load Current Rating:**

500.0 milliamperes resistive load second voltage

## **Contact Adjustability:**

Actuation point adjustable

## Contact Adjustment Range:

+0.20 to 15.00 actuation point gallons per minute

## Contact Adjustment Type:

External actuation point screw

## **Contact Voltage Rating In Volts:**

6.0 dc at sea level first voltage

## Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5930-00-138-2316

Flow Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A048b0

