

View Online at <https://aerobasegroup.com/nsn/5930-00-138-7189>

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Bushing Length:**

0.520 inches

**Body Length:**

1.940 inches

**Body Width:**

0.690 inches

**Body Height:**

0.920 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.330 inches

**Actuator Height:**

0.859 inches

**Actuator Free Position Height:**

1.529 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

10.0 ounces

**Switch Actuating Force:**

22.0 ounces

**Actuator Movement:**

0.050 pretravel inches and 0.219 overtravel inches and 0.007 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0