

View Online at <https://aerobasegroup.com/nsn/5930-00-138-7189>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.520 inches

Body Length:

1.940 inches

Body Width:

0.690 inches

Body Height:

0.920 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

0.859 inches

Actuator Free Position Height:

1.529 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

10.0 ounces

Switch Actuating Force:

22.0 ounces

Actuator Movement:

0.050 pretravel inches and 0.219 overtravel inches and 0.007 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0