

View Online at <https://aerobasegroup.com/nsn/5930-00-139-1257>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.282 inches single pressure connection

**Overall Length:**

3.000 inches

**Outside Diameter:**

0.438 inches single connection

**Body Length:**

1.700 inches

**Overall Diameter:**

0.850 inches

**Pressure Switch Type:**

Gage

**Width Across Flats:**

0.750 inches

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Mounting Method:**

Input port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch

**Thread Size:**

0.4375 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

7500.00 pounds per square inch

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

2500.00 actuation point pounds per square inch gage and 2000.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0