

View Online at <https://aerobasegroup.com/nsn/5930-00-139-1806>

**Body Style:**

Hole mounted

**Overall Length:**

1.380 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.125 inches

**Overall Height:**

0.680 inches

**Overall Width:**

0.540 inches

**Body Length:**

0.875 inches

**Body Width:**

0.460 inches

**Body Height:**

0.351 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.136 inches and 0.140 inches

**Actuator Length:**

0.278 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.030 inches

**Actuator Width:**

Between 0.210 inches and 0.225 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac and 125.0 dc

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, both positions maintained 1st switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

6.000 amperes resistive ac and 500.0 milliamperes resistive dc

**Special Features:**

Flush screw driver slotactuator

**Precious Material And Location:**

Terminal and contact surfaces silver

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0