## NSN 5930-00-139-2624

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-139-2624

| 0.000  |
|--|
| Overall Length:  |
| 4.688 inches   |
| Overall Height:  |
| 7.812 inches   |
| Overall Width:   |
| 1.625 inches   |
| Body Height:   |
| 2.750 inches   |
| Distance Between Mounting Facility Centers:  |
| 4.188 inches   |
| Capillary Tube Length:   |
| 180.000 inches   |
| Bulb Length:   |
| 4.218 inches   |
| Tempurature Sensing Element Type:  |
| Capillary tube-bulb  |
| Mounting Method:   |
| Bracket  |
| Features Provided:   |
| Electrical access port   |
| Contact Action Stimulus:   |
| Increase   |
| Mounting Facility Pattern:   |
|  |
| Two position in-line   |
| Two position in-line  Nonpile-up Contact Arrangement:  |
| ·  |
| Nonpile-up Contact Arrangement:  |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action   |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:   |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage   |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:   |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:   |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:  |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:  Internal deactuation point screw and internal actuation point screw   |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:  Internal deactuation point screw and internal actuation point screw  Contact Voltage Rating In Volts:                                       |
| Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:  Internal deactuation point screw and internal actuation point screw  Contact Voltage Rating In Volts:  230.0 ac at sea level single voltage |

Gas or liquid

## NSN 5930-00-139-2624

Thermostatic Switch - Page 2 of 2



| Style Designator: |
|-------------------|
| Rectangular       |
| Shelf Life:       |
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |

A048b0