## NSN 5930-00-139-2624

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-139-2624

0.000
Overall Length:
4.688 inches
Overall Height:
7.812 inches
Overall Width:
1.625 inches
Body Height:
2.750 inches
Distance Between Mounting Facility Centers:
4.188 inches
Capillary Tube Length:
180.000 inches
Bulb Length:
4.218 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Two position in-line  Nonpile-up Contact Arrangement:
·
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:  Internal deactuation point screw and internal actuation point screw
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:  Internal deactuation point screw and internal actuation point screw  Contact Voltage Rating In Volts:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  5.0 amperes resistive load single voltage  Contact Adjustability:  Deactuation point adjustable and actuation point adjustable  Contact Adjustment Range:  -30.00/+90.00 actuation point degrees fahrenheit and -28.00 to 88.00 deactuation point degrees fahrenheit  Contact Adjustment Type:  Internal deactuation point screw and internal actuation point screw  Contact Voltage Rating In Volts:  230.0 ac at sea level single voltage

Gas or liquid

## NSN 5930-00-139-2624

Thermostatic Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0