NSN 5930-00-139-2657

Rotary Switch - Page 1 of 2

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Thread Class:

Thread Length:

Dustproof

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-139-2657

4.094 inches Overall Diameter: 2.000 inches Individual Section Quantity: 3 Knob Manufacturer Code: 82121 Knob Manufacturer Part Number: D Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock Switch Contact Basic Design:
2.000 inches Individual Section Quantity: 3 Knob Manufacturer Code: 82121 Knob Manufacturer Part Number: D Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Individual Section Quantity: 3 Knob Manufacturer Code: 82121 Knob Manufacturer Part Number: D Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Knob Manufacturer Code: 82121 Knob Manufacturer Part Number: D Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Knob Manufacturer Code: 82121 Knob Manufacturer Part Number: D Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
82121 Knob Manufacturer Part Number: D Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Knob Manufacturer Part Number: D Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Knob Specificationial Markings: Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Arrow Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Nonturn Device Type: Flatted bushing at 12: 00 o'clock
Flatted bushing at 12: 00 o'clock
·
Switch Contact Basic Design:
-
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
4 each section rear
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.469 inches single mounting facility
Contact Voltage Rating In Volts:
125.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise and counterclockwise single actuator
Switch Actuator Indexing Position Quantity:
Switch Actuator Indexing Position Quantity: 8 single actuator

NSN 5930-00-139-2657

Rotary Switch - Page 2 of 2



Contact	Switching	Action:
CUIILACL	SWILCIIIII	ACLIOII.

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0