

View Online at <https://aerobasegroup.com/nsn/5930-00-139-2659>

Thread Class:

2a all threaded stud

Thread Length:

0.182 inches all threaded stud and 0.192 inches all threaded stud

Overall Height:

0.902 inches

Body Height:

0.395 inches

Overall Diameter:

0.640 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

177.00 actuation point degrees fahrenheit and 193.00 actuation point degrees fahrenheit and 7.00 differential point degrees fahrenheit and 33.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

96906-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0