

View Online at <https://aerobasegroup.com/nsn/5930-00-139-5720>

Overall Length:

2.250 inches

First Flat Length:

0.188 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Overall Diameter:

1.250 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Pin at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+10.000/+40.000 inch-ounces single actuator

Contact Load Current Rating:

750.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0