

View Online at <https://aerobasegroup.com/nsn/5930-00-140-1612>

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.183 inches

**Overall Height:**

Between 0.233 inches and 0.315 inches

**Body Diameter:**

0.650 inches

**Body Height:**

Between 0.218 inches and 0.293 inches

**Unthreaded Mounting Hole Diameter:**

0.104 inches

**Distance Between Mounting Facility Centers:**

0.937 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.5 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

180.00 actuation point degrees fahrenheit and 188.00 actuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 8.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0