

View Online at <https://aerobasegroup.com/nsn/5930-00-140-1612>

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.183 inches

Overall Height:

Between 0.233 inches and 0.315 inches

Body Diameter:

0.650 inches

Body Height:

Between 0.218 inches and 0.293 inches

Unthreaded Mounting Hole Diameter:

0.104 inches

Distance Between Mounting Facility Centers:

0.937 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.5 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

180.00 actuation point degrees fahrenheit and 188.00 actuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 8.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0