

View Online at <https://aerobasegroup.com/nsn/5930-00-141-0455>

Thread Class:

2a single mounting facility

Thread Length:

0.531 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.885 inches

First Flat Length:

0.250 inches 2nd actuator

Flat Height:

0.219 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.630 inches 1st actuator

Overall Diameter:

1.284 inches

Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

5 3rd section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

5 2nd actuator

Shaft Type:

Round, flatted all actuators

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Adjustable stop all actuators

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 100.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Common plate surfaces, contacts and terminals silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0