

View Online at <https://aerobasegroup.com/nsn/5930-00-141-0455>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.531 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

3.885 inches

**First Flat Length:**

0.250 inches 2nd actuator

**Flat Height:**

0.219 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.630 inches 1st actuator

**Overall Diameter:**

1.284 inches

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Operating Temperature Range:**

-65.0 to 85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

5 3rd section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Rotor Through Connection Quantity:**

2 each section

**Switch Actuator Indexing Position Quantity:**

5 2nd actuator

**Shaft Type:**

Round, flatted all actuators

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees all actuators

**Switch Actuator Stop Device Type:**

Adjustable stop all actuators

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 100.0 milliamperes inductive load dc at sea level

**Precious Material And Location:**

Common plate surfaces, contacts and terminals silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0