

View Online at <https://aerobasegroup.com/nsn/5930-00-142-4711>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

0.781 inches

Body Width:

0.258 inches

Body Height:

0.438 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.093 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

8.0 ounces

Actuator Movement:

Between 0.045 pretravel inches and 0.015 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0