NSN 5930-00-143-0709

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-00-143-0709

Explosion proof and humidity resistant
Overall Length:
3.096 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White and white single actuator
Illuminated Actuator Color:
Clear and yellow single actuator
Actuator Inscription:
Ro/arm single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
2.996 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit

NSN 5930-00-143-0709

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc

Special Features:

Actuator inscription is white and green

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0