

View Online at <https://aerobasegroup.com/nsn/5930-00-144-2058>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

4.000 inches

**Overall Height:**

5.750 inches

**Overall Width:**

2.312 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.250 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.625 inches

**Longest Vertical Distance Between Mounting Centers:**

3.312 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

12000.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+90.00 to 3300.00 actuation point pounds per square inch and +60.00/+3270.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point hex nut and internal actuation point hex nut

**Contact Stimulus Rating:**

3000.00 actuation point pounds per square inch and 30.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

250.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0