## NSN 5930-00-144-4105

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

**Body Style:**Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-00-144-4105

Overall Length:
3.096 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White and white single actuator
Illuminated Actuator Color:
Clear and yellow single actuator
Actuator Inscription:
Ctr/arm single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
2.996 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit

## NSN 5930-00-144-4105

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc

**Special Features:** 

Legend inscription is white and green

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0