# NSN 5930-00-145-9337

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-145-9337

## **Thread Class:**

2a single mounting facility

# Thread Length:

0.500 inches single mounting facility

# **Overall Length:**

1.895 inches

## **Overall Height:**

Between 1.235 inches and 1.265 inches

# **Overall Width:**

Between 0.990 inches and 1.010 inches

## Shaft Diameter:

0.249 inches single actuator and 0.251 inches single actuator

## Shaft Length:

1.000 inches single actuator

## Nonturn Device Radius:

0.365 inches at 3: 00 o'clock and 0.385 inches at 3: 00 o'clock

## Individual Section Quantity:

1

## Nonturn Device Type:

Tab at 3: 00 o'clock

# **Operating Tempurature Range:**

-40.0 to 85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section front

## **Throw Quantity:**

2 single section rear

# Mounting Method:

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

2 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section front

# NSN 5930-00-145-9337

Rotary Switch - Page 2 of 2



#### Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

350.0 milliamperes resistive load ac at sea level

## Style Designator:

Circular wafer, bushing mount

## **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0