

View Online at <https://aerobasegroup.com/nsn/5930-00-146-4126>

**Inside Diameter:**

0.125 inches all connections

**Overall Length:**

1.812 inches

**Overall Width:**

Between 4.594 inches and 4.656 inches

**Body Diameter:**

3.500 inches

**Body Length:**

1.812 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Distance Between Mounting Facility Centers:**

Between 4.219 inches and 4.281 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -54.0 degrees celsius and 55.0 degrees celsius

**Mounting Method:**

Flange and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

5.00 pounds per square inch

**Thread Size:**

0.125 inches all pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+0.40/+1.60 actuation point inches of water

**Contact Adjustment Type:**

External actuation point pointer

**Contact Voltage Rating In Volts:**

240.0 ac at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0