NSN 5930-00-146-5024

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-146-5024

| Body Style: |
|--|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Bushing Length: |
| 0.470 inches |
| Body Length: |
| 1.310 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.875 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 1.125 inches |
| Actuator Width: |
| 0.375 inches |
| Actuator Position-action Relationship: |
| Up position momentary and down position momentary and center position maintained |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac |
| End Application: |
| Cargo system, 463I |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Actuator seal |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, two positions momentary single switch unit |
| Criticality Code Justification: |

Feat

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

NSN 5930-00-146-5024

Toggle Switch - Page 2 of 2



Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0