NSN 5930-00-146-8583

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-146-8583

Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.537 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Leaf
Actuator Width:
0.160 inches
Actuator Free Position Height:
0.350 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
7.0 ounces
Actuator Movement:
Between 0.219 pretravel inches and 0.030 overtravel inches and 0.030 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug

NSN 5930-00-146-8583

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0