NSN 5930-00-147-0696

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-147-0696 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Body Length:** 1.940 inches **Body Width:** 0.687 inches **Body Height:** 1.150 inches **Unthreaded Mounting Hole Diameter:** 0.139 inches **Actuator Length:** 2.500 inches **Actuator Style:** Leaf **Actuator Free Position Height:** 0.750 inches **Maximum Voltage Rating In Volts:** 400.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 0.5 ounces **Switch Actuating Force:** 1.0 ounces **Actuator Movement:** Between 0.578 overtravel inches and 0.145 differential inches stive ac

| Contact Load Current Rating At Maximum Rated Voltage |
|--|
| 250.000 milliamperes resistive dc and 15.000 amperes resis |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| |
| |

NSN 5930-00-147-0696

Sensitive Switch - Page 2 of 2



Fiig:

A053a0