

View Online at <https://aerobasegroup.com/nsn/5930-00-147-0762>

Thread Class:

2a single mounting facility

Thread Length:

0.417 inches and 0.452 inches single mounting facility

Overall Length:

1.974 inches

First Flat Length:

0.230 inches and 0.270 inches single actuator

Flat Height:

0.204 inches and 0.224 inches single actuator

Shaft Diameter:

0.248 inches and 0.251 inches single actuator

Shaft Length:

0.417 inches and 0.457 inches single actuator

Overall Diameter:

1.187 inches

Nonturn Device Radius:

0.360 inches and 0.390 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-65.0 to 125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.5 amperes resistive load ac at sea level 100.0 milliamperes inductive load and 1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0