

View Online at <https://aerobasegroup.com/nsn/5930-00-147-0762>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.417 inches and 0.452 inches single mounting facility

**Overall Length:**

1.974 inches

**First Flat Length:**

0.230 inches and 0.270 inches single actuator

**Flat Height:**

0.204 inches and 0.224 inches single actuator

**Shaft Diameter:**

0.248 inches and 0.251 inches single actuator

**Shaft Length:**

0.417 inches and 0.457 inches single actuator

**Overall Diameter:**

1.187 inches

**Nonturn Device Radius:**

0.360 inches and 0.390 inches at 3: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-65.0 to 125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 30.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.5 amperes resistive load ac at sea level 100.0 milliamperes inductive load and 1.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0