

View Online at <https://aerobasegroup.com/nsn/5930-00-147-9449>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.789 inches

Body Width:

0.250 inches

Body Height:

0.480 inches

Unthreaded Mounting Hole Diameter:

0.094 inches

Actuator Length:

0.296 inches

Actuator Style:

Leaf

Actuator Width:

0.110 inches

Actuator Free Position Height:

0.408 inches

Actuator Adapter Style:

Leaf

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.014 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes resistive ac and 2.000 amperes inductive ac

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0