

View Online at <https://aerobasegroup.com/nsn/5930-00-148-4528>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

0.781 inches

Body Width:

0.290 inches

Body Height:

0.761 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.656 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.720 inches

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.012 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 5.000 amperes inductive dc and 8.000 amperes resistive ac and 5.000 amperes resistive ac

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0