

View Online at <https://aerobasegroup.com/nsn/5930-00-148-4528>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

0.781 inches

**Body Width:**

0.290 inches

**Body Height:**

0.761 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Length:**

0.656 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.720 inches

**Actuator Roller Diameter:**

0.188 inches

**Actuator Roller Width:**

0.125 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

16.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.012 overtravel inches and 0.025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

8.000 amperes resistive dc and 5.000 amperes inductive dc and 8.000 amperes resistive ac and 5.000 amperes resistive ac

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0