

View Online at <https://aerobasegroup.com/nsn/5930-00-149-9843>

**Hazardous Locations/environmental Protection:**

Raintight

**Capillary Tube Length:**

120.000 inches

**Bulb Length:**

2.500 inches

**Bulb Diameter:**

0.290 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.640 inches

**Shortest Horizontal Distance Between Mounting Centers:**

2.320 inches

**Longest Vertical Distance Between Mounting Centers:**

3.531 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Bracket

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Contact Load Current Rating:**

22.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+0.00 to 150.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal actuation point knob

**Contact Voltage Rating In Volts:**

277.0 ac at sea level single voltage

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0