

View Online at <https://aerobasegroup.com/nsn/5930-00-149-9843>

Hazardous Locations/environmental Protection:

Raintight

Capillary Tube Length:

120.000 inches

Bulb Length:

2.500 inches

Bulb Diameter:

0.290 inches

Longest Horizontal Distance Between Mounting Centers:

4.640 inches

Shortest Horizontal Distance Between Mounting Centers:

2.320 inches

Longest Vertical Distance Between Mounting Centers:

3.531 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Contact Load Current Rating:

22.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.00 to 150.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point knob

Contact Voltage Rating In Volts:

277.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0