

View Online at <https://aerobasegroup.com/nsn/5930-00-150-1016>

Thread Class:

3a single pressure connection

Thread Length:

1.125 inches single pressure connection

Overall Length:

3.875 inches

Outside Diameter:

0.750 inches single connection

Overall Height:

2.312 inches

Overall Width:

2.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

800.00 pounds per square inch

Thread Size:

0.750 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

1200.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

60.0 milliamperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

5.00 actuation point gallons per minute and 1.00 deactuation point gallons per minute and 4.00 differential point gallons per minute

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Gasket seal, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0